

Intrinsically Safe Digital Thermometers

#### 3208 IS Model

The 3208IS Thermometer & Probes are Category 1 certified **for use in flammable or explosive atmospheres**. Their tough construction makes them extremely durable and therefore functional, not only in hazardous atmospheres but also hostile working environments.

**ATEX – where safety is critical**. The 3208 IS Digital Thermometers represent the best in temperature measurement technology for use in dangerous environments.

Certified by BASEEFA, the UK's leading Intrinsic Safety approvals house, the units are classified as EEx ia IIC T4.

This certification is equivalent to EN60079-0:2004 and EN50020:2002. The units are ready for site use anywhere, immediately.

# General Specification

Resolution:	0.1°C or 1°C
	0.1°C resolution: 0.2% reading + 0.5°C (-50°C to +199.9°C)
Accuracy:	1°C resolution: 0.2% reading + 1° C (-50°C to +950°C)
	Excluding Probe Error – Refer to IEC 60584 2013
Operating Temperature (ambient):	-20 to +50°C
Temperature range:	Low -50°C to +199.9°C
Temperature range.	High -50°C to +950°C
Battery Type:	9V PP3 Style zinc chloride IEC style 6F22 (Type PP3S or equivalent)
Battery Life:	100 hours typical
Dianlay	12.7mm/0.5 sustam LCD with sutamatic lagand display
Display:	12.7mm/0.5 custom LCD with automatic legend display
Low Battery Check:	
	'BAT shows on display'
Low Battery Check:	'BAT shows on display' °C displayed
Low Battery Check: Sensor Open Circuit:	'BAT shows on display' °C displayed BS5490:IP64 standard
Low Battery Check: Sensor Open Circuit: Environmental Specifications:	'BAT shows on display' °C displayed BS5490:IP64 standard 140 x 70 x 26mm/55 x 2.8 x 1.0
Low Battery Check: Sensor Open Circuit: Environmental Specifications: Dimensions: Weight:	'BAT shows on display' °C displayed BS5490:IP64 standard 140 x 70 x 26mm/55 x 2.8 x 1.0
Low Battery Check: Sensor Open Circuit: Environmental Specifications: Dimensions:	<ul> <li>'BAT shows on display'</li> <li>°C displayed</li> <li>BS5490:IP64 standard</li> <li>140 x 70 x 26mm/55 x 2.8 x 1.0</li> <li>250g/8.8oz</li> <li>K0234IS - 100mm Shaft , General Purpose Probe</li> </ul>



3208 IS Model

#### For other options, please contact us sales@digitron-italia.it or +39 (0)775 392052

#### **Key Features and Benefits**

- Certifed to EEx ia IIC T4
- Highly Accurate
- Tough enclosure construction adds to durability
- Quality electronics give excellent reliability
- Easy to use

### Main Applications

A **world leader** in digital thermometers, Digitron has become the standard for accurate and reliable measurement across the following industries:



Flammable and/or explosive atmospheres

### **Technical Certification**

- Certificate of Conformity
- Factory Test Certificate
- Factory Calibration Certificate


#### **Export Documentation**

- Certificate of Origin
- EUR1
- ATR

## Calibration and After-Sales Support

- Fully trained field service personnel
- Use of UKAS certified calibration equipment
- 5 day turnaround
- Fixed pricing
- Approved manufacturer parts
- Full post-service reports
- 12 month warranty





For more information, please contact our service team service@digitron-italia.it